Nova LFS HEV

Combining diesel and hybrid technologies



Reduces fuel consumption and emissions by up to 30% Hybrid buses can lead to significant gains in fuel efficiency as well as leading to further service improvements in exhaust and noise emissions for specific areas.

Hybrid technology is perfect in frequent stop and go conditions. There's a solution for every city.



Nova LFS HEV



BETTER FUEL ECONOMY

Up to 30% fuel savings at average speeds of 9-18 mph

REDUCED MAINTENANCE COSTS

Savings on brakes and engine maintenance costs from regenerative braking

REDUCED EMISSIONS

Lowers NOx, PM, CO and HC emissions by up to 40%

Specifications

LENGTH	40′ (12.19m)
WIDTH	102" (2.59m)
HEIGHT	10′ 11′′ (3.33m)
INTERIOR HEIGHT	93" (2.36m) excluding rear axle 74" (1.88m) over rear axle
WHEELBASE	Front to rear axle: 244 inches
SEATING CAPACITY	Up to 41 passengers
LOADING CAPACITY	Up to 75 passengers
STRUCTURE	Stainless steel
CORROSION-RESISTANT OUTSIDE SHELL	Fiberglass and thermoplastic skirt panels
ENGINE OPTIONS	Cummins B6.7 280
ROOF-MOUNTED HVAC OPTIONS	Mobile Climate Control Eco 136e electric, Thermo King AM2 all-electric
FLOORING SYSTEM	Composite
DOOR WIDTH	35 inches (standard) or 47 inches (wide)
ELECTRIC / ELECTRONIC SYSTEM	Volvo Multiplex System (VBEA)
TRANSMISSION OPTIONS	BAE HDS200, Allison H 40 EP
RADIATOR	Nova eCooling system
AXLES	ZF RL-82 (Front), ZF AV-132 (Rear)
BRAKE SYSTEM	ABS all-wheel disc brakes with traction control
FUEL TANK CAPACITY	125 gallons
TURNING RADIUS	40′ 10″ (12.45m)

